

Series:HTK

Model	Refrigerant	Rated Voltage [V]	Frequency [Hz]	Displacement [cc]	Motor Type	Cooling Capacity		COP without R.C.		COP with R.C.		Approval	Height [mm]	Net Weight [Kg]
						ASHRAE	CECOMAF	ASHRAE	CECOMAF	ASHRAE	CECOMAF			
						-23.3°C	-25°C	-23.3°C	-25°C	-23.3°C	-25°C			
						[W]	[W]	[W/W]	[W/W]	[W/W]	[W/W]			
HTK55AA	R600 a	220-240	50	5.6	RSIR/RSCR	93	69	1.55	1.21	1.61	1.25	VDE, CE	159	7.8
HTK70AA	R600 a	220-240	50	6.6	RSIR/RSCR	117	87	1.61	1.25	1.66	1.30	VDE, CE	159	7.8
HTK80AA	R600 a	220-240	50	8.1	RSIR/RSCR	136	102	1.61	1.26	1.66	1.31	VDE, CE	159	7.9
HTK95AA	R600 a	220-240	50	9.6	RSIR/RSCR	167	126	1.64	1.29	1.70	1.34	VDE, CE	167	8.3
HTK12AA	R600 a	220-240	50	11.1	RSIR/RSCR	198	149	1.64	1.28	1.70	1.34	VDE, CE	167	8.4